

CM4732V201R-10




PHYSICAL DIMENSIONS:

A	11.94 [.470]	+ 0.18 [.007]
B	8.13 [.320]	+ 0.13 [.005]
B1	10.92 [.430]	MAX
C	9.45 [.372]	+ 0.15 [.006]
C1	10.08 [.397]	MAX
D	4.06 [.160]	+ 0.05 [.002]
E	1.27 [.050]	+ 0.13 [.005]
E1	2.03 [.080]	+ 0.13 [.005]

WIRE DIMENSIONS:

T1	3.30 [.130]	+ 0.38 [.015]
T2	0.64 [.025]	TYP
T3	0.38 [.015]	TYP





ELECTRICAL CHARACTERISTICS:

Z @ 100MHz (Ω)	DCR (Ω)	Rated Current
Nominal	200	
Minimum	150	
Maximum	250	8,000 mA


NOTES: UNLESS OTHERWISE SPECIFIED

1. TAPED AND REELED per CURRENT EIA SPECIFICATIONS 13" REELS, 400 PCS/REEL.
2. COMPONENTS SHOULD BE ADEQUATELY PREHEATED BEFORE SOLDERING.
3. REF. CARRIER TAPE SPECIFICATION #CART4732-23.
4. TERMINATION FINISH IS 100% TIN.
5. THIS PART HAS NO PIN POLARITY.


UNCONTROLLED DOCUMENT




LAND PATTERNS FOR REFLOW SOLDERING



EQUIVALENT CIRCUIT



RECOMMENDED SOLDERING CONDITIONS



DIMENSIONS ARE IN mm (INCHES).

This print is the property of Laird Tech. and is loaned in confidence subject to return upon request and with the understanding that no copies shall be made without the written consent of Laird Tech. All rights to design or invention are reserved.



C	UPDATE COMPANY LOGO & KAPTON KAPTON LABEL ADD EQUIV. CIRCUIT	11/11/08	JRK	PROJECT/PART NUMBER: CM4732V201R-10	REV C	PART TYPE: ASSEMBLY	DRAWN BY: JRK
B	UPDATE COMPANY LOGO	12/11/07	JRK	DATE: 06/03/04	SCALE: NTS	SHEET:	
A	ORIGINAL DRAFT	06/03/04	JRK	CAD #	TOOL #		
REV	DESCRIPTION	DATE	INT	CM4732V201R-10-C-2	H0470-2		2 of 3